

## HARDWARE FEATURES

Interface	24× PoE+ 10/100 Mbps RJ45 Ports 2× 10/100/1000 Mbps RJ45 Ports 2× Combo Gigabit SFP Slots
Network Media	10BASE-T: UTP category 3, 4, 5 cable (maximum 100m) EIA/TIA-568 100Ω STP (maximum 100m) 100BASE-TX: UTP category 5, 5e cable (maximum 100m) EIA/TIA-568 100Ω STP (maximum 100m) 1000BASE-T: UTP category 5, 5e, 6 or above cable (maximum 100m) EIA/TIA-568 100Ω STP (maximum 100m) 1000BASE-X MMF, SMF
Fan Quantity	2 Fans
Physical Security Lock	Yes
Power Supply	100-240 VAC, 50/60 Hz
Backup Bandwidth	8.8 Gbps
PoE+ Ports(RJ45)	Standard: 802.3at/802.3af compliant PoE Ports: Port 1 – Port 24 PoE Power Budget: 250 W
Mac Address Table	8 K
Dimensions ( W x D x H )	17.3 × 7.1 × 1.7 in (440 × 180 × 44 mm)
Max Power Consumption	18.32 W (220/50 Hz. no PD connected) 294 W (220/50 Hz. with 250 W PD connected)
Max Heat Dissipation	62.47 BTU/h (no PD connected) 1002.54 BTU/h (with 250 W PD connected)

## SOFTWARE FEATURES

Advanced Features	Compatible With IEEE 802.3at/af Compliant PDs Extend Mode (Up to 250m PoE power supply and data transmission) Priority Mode Isolation Mode PD Detection Intelligent Power Supply Mac Address Auto-Learning and Auto-Aging IEEE802.3x Flow Control
Transmission Method	Store-And-Forward

## OTHERS

Certification	CE, FCC, RoHS
Package Contents	TL-SL1226P Power Cable Installation Guide Two mounting brackets and the fittings
Environment	Operating Temperature: 0–50 °C (32–122 °F) Storage Temperature: -40–70 °C (-40–158 °F) Operating Humidity: 10–90% non-condensing Storage Humidity: 5–90% non-condensing