

HARDWARE FEATURES

Interface	2 10/100/1000Mbps RJ45 Port AUTO Negotiation/AUTO MDI/MDIX 1 48VDC POWER INPUT PORT
Network Media	10BASE-T: UTP category 3, 4, 5 cable (Max 100m) EIA/TIA-568 100Ω STP (Max 100m) 100BASE-TX: UTP category 5, 5e cable (Max 100m) EIA/TIA-568 100Ω STP (Max 100m) 1000BASE-T: UTP category 5, 5e, 6 cable (Max 100m)
Power Supply	15.4W (Max. 48VDC)
LED Indicator	PWR
Dimensions (W x D x H)	3.2 × 2.1 × 0.9 in. (81 × 54 × 24 mm)

SOFTWARE FEATURES

Basic Function	Compatible With IEEE 802.3af Compliant PDs Delivers Power Up To 100 Meters Auto-Determine The Necessary Power Requirements
----------------	--

OTHERS

Certification	FCC, RoHS
Package Contents	Gigabit PoE Injector TL-POE150S Power Adapter RJ45 Cable Installation Guide
Environment	Operating Temperature: 0°C~40°C (32°F~104°F) Storage Temperature: -40°C~70°C (-40°F~158°F) Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~90% non-condensing