

## HARDWARE FEATURES

Standards and Protocols	IEEE 802.3, 802.3u, 802.3x, TCP/IP, DHCP, ICMP, NAT, PPPoE, SNTP, HTTP, DDNS
Interface	1 Fixed 10/100 Ethernet WAN Port 1 Fixed 10/100 Ethernet LAN Port 3 Changeable 10/100 Ethernet WAN/LAN Ports
Network Media	10BASE-T: UTP category 3, 4, 5 cable (Max 100m) 100BASE-TX: UTP category 5, 5e cable (Max 100m)
Button	Reset Button
Power Supply	External 9V/0.6A DC Adapter
Flash	16MB
DRAM	128MB
LED	PWR, SYS, WAN, LAN, WAN/LAN
Dimensions ( W x D x H )	6.2 × 4.0 × 1.0 in. (158 × 101 × 25mm)

## PERFORMANCE

Concurrent Session	10K
--------------------	-----

## BASIC FUNCTIONS

WAN Connection Type	Static/Dynamic IP, PPPoE, PPTP, L2TP, Dual Access, Bigpond Cable
DHCP	DHCP Server/Client, DHCP Address Reservation
MAC Clone	Modify WAN/LAN MAC Address
Switch Setting	Rate Control, Port Configuration, Port VLAN

## ADVANCED FUNCTIONS

ACL	IP/MAC/URL/WEB Filtering
IGMP	IGMP Proxy/IGMP Snooping
Forwarding	Virtual Server, Port Triggering, DMZ
Load Balance	Policy Routing, Link Backup
Routing	Static Routing
Security	FTP/SIP/PPTP/IPsec/H.323 ALG, DoS Defence, Ping of Death, IP/MAC Binding
Traffic Control	Bandwidth Control, Session Limit

## MANAGEMENT

Service	Dynamic DNS, UPnP
---------	-------------------

## MANAGEMENT

Maintenance	System Time Setting Daylight Saving Time SNMP Diagnostics Firmware Upgrade Factory Defaults/Reboot Backup/Restore System Log Remote Management System Statistics
-------------	---

## OTHERS

Certification	CE, FCC, RoHS
Package Contents	TL-R470T+ Power Adapter RJ-45 Ethernet Cable Quick Installation Guide
Environment	Operating Temperature: 0°C~40°C (32°F~104°F) Storage Temperature: -40°C~70°C (-40°F~158°F) Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~90% non-condensing