

HARDWARE FEATURES

Standards and Protocols	IEEE 802.3, 802.3u, 802.3x, TCP/IP, DHCP, ICMP, NAT, PPPoE, SNTP, HTTP, DDNS
Interface	1 Fixed 10/100 Ethernet WAN Port 1 Fixed 10/100 Ethernet LAN Port 3 Changeable 10/100 Ethernet WAN/LAN Ports
Network Media	10BASE-T: UTP category 3, 4, 5 cable (Max 100m) 100BASE-TX: UTP category 5, 5e cable (Max 100m)
Button	Reset Button
Power Supply	Internal Universal Power Supply AC100-240V~50/60Hz input
Flash	16MB
DRAM	128MB
LED	PWR, SYS, WAN, LAN, WAN/LAN
Dimensions (W x D x H)	11.6 x 7.1 x 1.7in. (294 x 180 x 44mm) 13-inch / 19-inch Standard Rack-Mount Width, 1U Height

PERFORMANCE

Concurrent Session	30K
--------------------	-----

BASIC FUNCTIONS

WAN Connection Type	Static/Dynamic IP, PPPoE, PPTP, L2TP, Dual Access, Bigpond Cable
DHCP	DHCP Server/Client, DHCP Address Reservation
MAC Clone	Modify WAN/LAN MAC Address
Switch Setting	Port Mirror, Rate Control, Port Configuration, Port VLAN

ADVANCED FUNCTIONS

ACL	IP/MAC/URL/WEB Filtering
IGMP	IGMP Proxy/IGMP Snooping
Forwarding	Virtual Server, Port Triggering, DMZ
Load Balance	Policy Routing, Link Backup
NAT	One-to-One NAT, Multi-Nets NAT
Routing	Static Routing
Security	FTP/SIP/PPTP/IPsec/H.323 ALG, DoS Defence, Ping of Death
Traffic Control	Bandwidth Control, Session Limit

MANAGEMENT

MANAGEMENT

Service	Dynamic DNS, UPnP
Maintenance	System Time Setting Daylight Saving Time SNMP Diagnostics Firmware Upgrade Factory Defaults/Reboot Backup/Restore System Log Remote Management Statistics

OTHERS

Certification	FCC, RoHS
Package Contents	TL-R480T+ Power Cord RJ-45 Ethernet Cable Installation Guide Rack-mount Kit
Environment	Operating Temperature: 0°C~40°C (32°F~104°F) Storage Temperature: -40°C~70°C (-40°F~158°F) Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~90% non-condensing