

HARDWARE FEATURES

Standards and Protocols	IEEE 802.3, IEEE802.3u, IEEE802.3ab TCP/IP, DHCP, ICMP, NAT, PPPoE, SNTP, HTTP, DNS, PPTP, L2TP
Interface	1 Gigabit WAN port 3 Gigabit LAN/WAN ports 1 Gigabit LAN port
Network Media	10BASE-T: UTP category 3, 4, 5 cable (Max 100m) EIA/TIA-568 100Ω STP (Max 100m) 100BASE-TX: UTP category 5, 5e cable (Max 100m) EIA/TIA-568 100Ω STP (Max 100m) 1000BASE-T: UTP category 5, 5e, 6 cable (Max 100m)
Button	Reset Button
Power Supply	Internal Universal Power Supply AC100-240V~ 50/60Hz Input
Flash	32MB
DRAM	DDRIII 256MB
LED	PWR, SYS, Link/Act, Speed, WAN
Dimensions (W x D x H)	17.3 x 8.7 x 1.7 in.(440x220x44 mm) 19-inch Standard Rack-Mount Width, 1U Height

PERFORMANCE

Concurrent Session	150K
NAT Throughput	800Mbps
NAT(iMIX)	703Mbps
NAT(DHCP)	934Mbps
NAT(PPPoE)	868Mbps

BASIC FUNCTIONS

WAN Connection Type	Static/Dynamic IP PPPoE/Russian PPPoE PPTP/Russian PPTP L2TP/Russian L2TP Bigpond Cable
DHCP	DHCP Server/Client DHCP Address Reservation
MAC Clone	Modify WAN MAC Address
IPTV	Bridge, Custom
IPv6	IPv6 Support
VLAN	802.1Q VLAN, Port VLAN

TRANSMISSION

TRANSMISSION

Load Balance	Intelligent Load Balance Link Backup (Timing, Failover) Online Detection
NAT	One-to-One NAT Multi-nets NAT Virtual Server Port Triggering FTP/H.323/SIP/IPsec/PPTP ALG UPnP
Routing	Static Routing Policy Routing
Session Limit	IP-based Session Limit
Bandwidth Control	IP-based Bandwidth Control

SECURITY

Attack Defense	TCP/UDP/ICMP Flood Defense Block TCP Scan (Stealth FIN/Xmas/Null) Block Ping from WAN
Filtering	MAC Filtering URL/Keywords Filtering
ARP Inspection	Sending GARP Packets ARP Scanning by WAN/LAN IP-MAC Binding
Access Control	Source/Destination IP Based Access Control

AUTHENTICATION

Web Authentication	Local User Authentication Radius Sever Authentication Onekey Online
--------------------	---

MANAGEMENT

Service	Dynamic DNS (Dyndns, No-IP)
Maintenance	Web Management Interface Remote Management Export & Import Configuration SNMP Diagnostics(Ping & Traceroute) NTP Synchronize Syslog Support

OTHERS

Certification	FCC, RoHS
Package Contents	TL-ER5120 Power Cord Rack-mount Kit Installation Guide

OTHERS

Environment

Operating Temperature: 0°C~40°C (32°F~104°F)
Storage Temperature: -40°C~70°C (-40°F~158°F)
Operating Humidity: 10%~90% non-condensing
Storage Humidity: 5%~90% non-condensing